

STANDARD FEATURES


- √ 26" compact fireplace with 9-1/2" depth allows for easy renovation to existing rooms
- Millivolt (Remote-ready) or thermostat control
- 99.9% heating efficiency
- Single row of dancing yellow flames
- Detailed ceramic fiber logs
- ♠ Durable textured powder-coat paint exterior/Standard black painted interior
- Arch screen with rolled louvered front
- 20 year limited warranty


REMOTE



Remote Control

^{*}All applicable models comply with ANSI Z21.50/88 barrier requirements.





	VCM3026	
Α	25-7/8"	
В	26-3/4"	
С	9-1/2"	
D	12-1/2"	
E	26"	


IMPORTANT NOTES:

As with any heating appliance, fireplace or stove, this appliance is extremely hot during operation. Read and understand all operating instructions before using this appliance. For further information, consult your dealer.


Local conditions, such as elevation and choice of fuel will affect overall appearance of the fire and heating performance. Performance can also vary with home design and insulation, ceiling height, accessories chosen and appliance location.

Diagrams, illustrations and photographs are not to scale — consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without

Built to ANSI Z21.11.2 standard and approved by PFS Test Laboratories. Consult your distributor for local fireplace code information.



Models	A	В	С
VCM3026	26-7/8"	26-7/8"	10-1/2"
	683 mm	683 mm	267 mm



Models	D	E	F	G
VCM3026	36-5/8"	25-7/8"	51-3/4"	26-7/8"
	931 mm	658 mm	1315 mm	683 mm

FIREPLACE EFFICIENCIES						
FUEL	BTU/HR	AFUE*				
NG	14,000-26,000	99.9%				
LP	14,000-26,000	99.9%				
NG	14,000-26,000	99.9%				
LP	14,000-26,000	99.9%				
	FUEL NG LP NG	FUEL BTU/HR NG 14,000-26,000 LP 14,000-26,000 NG 14,000-26,000				

*Annual Fuel Utilization Efficiency (AFUE) is the recognized U.S. rating system for the total efficiency of heating products.



Visit us online SuperiorFireplaces.us.com





