VRE6000 SERIES

OUTDOOR: VENT-FREE GAS FIREBOXES





FEATURES

- Available in 36", 42" and 50" models
- 30" tall, full brick to-face-design opening on all models.
- Fully insulated firebox for increased performance in colder climates
- Mosaic Masonry Firebrick available in a variety of patterns and colors with integrated ash lip (one required)
- Durable 304-stainless steel on front face, and all surfaces exposed to weather.
- Includes stainless steel mesh fire screens
- Select from a variety of compatible vent-free log sets and controls (sold separately)
- Easy-access gas line knockouts on both sides for quick and simple installation.
- 20 Year Limited Warranty

Compatible with any listed ANSI Z21.11.2 vent-free gas log set. Choose a Superior vent-free gas log set for best results.

INTERIOR OPTIONS

MOSAIC MASONRY FIREBRICK LINERS



Midnight Full Herringbone



Midnight Full Stack



Warm Red Full Herringbone



Warm Red Full Stack



Midnight Split Herringbone



Midnight Split Stack





Warm Red Split Herringbone Warm Red Full Stack



Slate Grey Full Herringbone



Slate Grey Full Stack



Ivory Full Herringbone



Ivory Full Stack



Slate Grey Split Herringbone Slate Grey Split Stack





Ivory Split Herringbone



Ivory Split Stack


COMPATIBLE VENT-FREE GAS LOG SETS




Giant Timbers OD



Mossy Oak OD





	VRE6036	VRE6042	VRE6050
G	29"	30-5/16"	38-5/16"
Н	45-1/8"	51-1/8"	59"
1	30"	30"	30"
J	36"	42"	50"
K	49"	49"	49"
L	28"	30"	28-1/2"
М	54-1/2"	54-1/2"	54-1/2"
N	3-5/16"	3-5/16"	3-5/16"
0	9-7/16"	9-7/16"	9-7/16"
Р	7-3/8"	8-3/4"	8-3/4"
Q	11-1/8"	13"	13"


IMPORTANT NOTES:

As with any fireplace, this appliance is extremely hot during operation. Read and understand all operating instructions before using this appliance. For further information, consult your dealer.

Local conditions, such as elevation and choice of fuel will affect overall appearance of the fire and heating performance. Performance can also vary with home design and insulation, ceiling height, accessories chosen and appliance location.


Diagrams, illustrations and photographs are not to scale — consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.

On the Cover: VRE6042 shown with Warm Red Herringbone brick



	VRE6036	VRE6042	VRE6050	
Α	54-5/8"	54-5/8"	54-5/8"	
В	45-3/8"	51-3/8"	59-1/4"	
С	28-1/4"	30-1/8"	30-1/8"	

CORNER FRAMING SPECIFICATIONS



	VRE6036	VRE6042	VRE6050	
D	61"	65"	71"	
E	45-3/8"	51-3/8"	59-3/8"	
F	86-1/2"	92"	100"	

INTERIOR FIREBOX DIMENSIONS*

	VRE6036	VRE6042	VRE6050	
FRONT WIDTH	36"	42"	50"	
REAR WIDTH	22 1/2"	26 3/8"	34 3/8"	
DEPTH	19"	21 3/4"	21 3/4"	
HEIGHT	30"	30"	30"	

^{*} To assist with compatible log size selection





