



Cat. No. PLF3614-XS

Notes

## Section 10309 – Manufactured Electric Fireplaces

### PART 1 GENERAL

#### 1.1 SECTION INCLUDES

- A. Manufactured electric fireplaces.
- B. Accessories.

#### 1.2 RELATED SECTIONS

- A. Section 06100 - Rough Carpentry: Wood framed rough opening and enclosure.

#### 1.3 REFERENCES

- A. UL - 2021
- B. CSA - C22.2 No. 46

#### 1.4 SUBMITTALS

- A. Submit under provisions of Section 01300.
- B. Product Data: Manufacturer's data sheets on each product to be used, including:
  - 1. Preparation instructions and recommendations.
  - 2. Storage and handling requirements and recommendations.
  - 3. Installation methods.
- C. Manufacturer's Certificates: Certify products meet or exceed specified requirements.
- D. Manufacturer's warranty.

#### 1.5 DELIVERY, STORAGE, AND HANDLING

- A. Store products in manufacturer's unopened packaging until ready for installation.
- B. Protect materials from exposure to moisture. Do not deliver until after wet work is complete and dry.

#### 1.6 WARRANTY

- A. Provide the manufacturers 2 year limited warranty on labor and electrical components.

### PART 2 PRODUCTS

#### 2.1 ACCEPTABLE MANUFACTURERS

- A. Pre-fabricated Electric Fireplace:
  - 1. Base: Dimplex Electric Fireplace
    - Glen Dimplex Americas
    - 1367 Industrial Road
    - Cambridge ON N3H 4C3
    - 1-888-DIMPLEX
    - www.dimplex.com



Cat. No. PLF3614-XS

Notes

## Section 10309 – Manufactured Electric Fireplaces

- archdesign@dimplex.com
- 2. Substitutions not permitted
- 3. Requests for substitutions will be considered in accordance with provisions of Section 01600.

### 2.2 ELECTRIC FIREPLACES

- A. General:
  - 1. Provide all components and accessories required for a complete, functional unit.
  - 2. UL or CSA listed.
- B. Pre-fabricated Electric Fireplace:
  - 1. Base Product:
    - a) Dimplex Linear Electric Fireplace
    - b) Model Number: PLF3614-XS
  - 2. Description: Realistic 36" wall-mount linear electric fireplace
  - 3. Dimensions:
    - a) Width 37-1/4" / 946mm
    - b) Height: 19-1/2" / 497mm
    - c) Depth: 3-3/4" / 97mm
  - 4. Framing Dimensions:
    - a) Width: 37" / 939.8mm
    - b) Height: 19" / 356mm
    - c) Depth: 3-1/2" / 89mm
  - 5. Electrical:
    - a) Volts: 120
    - b) Watts: 1500
    - c) BTUs: 5000
    - d) Amps: 12.5
  - 6. Venting: Non-venting
  - 7. Operation: Flame only, flame and heat
  - 8. Heating: Louver-less, fan-forced circulation
  - 9. Liner: Steel
  - 10. Standard features:
    - a) Flame/media bed on/off, range of color themes
    - b) Acrylic crystal ember bed with sparkle effect
    - c) LED flame technology
    - d) Pre-set and custom color effects
    - e) On-demand heater
    - f) Built-in hidden touch controls
    - g) Built-in Timer - Set for up to 8 hours.
    - a) Seamless installation and edge to edge glass
    - b) Integrated self-diagnostics reduce trouble shooting time and improve service and lead times for components.

## Section 10309 – Manufactured Electric Fireplaces

1. Control options:
  - a) Multi-function remote control
  - b) Built-in hidden touch controls (Flame on/off, heat on/off, thermostat, colour options)

### PART 2 EXECUTION

#### 2.1 INSPECTION

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.
- C. Verify proper power supply and fuel source are available.

#### 2.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

#### 2.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions and requirements of authorities having jurisdiction.
- B. Use manufacturer's guidelines for minimum clearances to combustibles, walls, and finishes.
- C. Anchor all components firmly in position for long life under hard use.
- D. Upon completion of installation, visually inspect all exposed surfaces. Touch up scratches and abrasions with touch up paint recommended by the manufacturer; make imperfections invisible to the unaided eye from a distance of 5 feet (1.5 m).

#### 2.4 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

**END OF SECTION**